

LOAD AND INFLATION TABLES

TBR Load Inflation Tables

TIRE LOAD LIMITS (LBS.) AT VARIOUS COLD INFLATION PRESSURES

• NEVER exceed the sidewall markings for the maximum loads and inflation pressures

Note: Letters in parentheses denote Load Range for which Bold Face loads are maximum. International Load Index numbers are shown after the Load Range.

Tire Size	PSI		70	75	80	85	90	95	100	105	110	115	120	125	130	
215/75R17.5	Dual	lbs.	2570	2715	2860	3000	3140	3280	3420(F) 123							
	Single		2650	2800	2950	3095	3240	3385	3530(F) 124							
215/75R17.5	Dual	lbs.	2550	2695	2835	2980	3120	3255	3390	3525(G) 124						
	Single		2710	2865	3015	3165	3310	3460	3605	3750(G) 126						
225/70R19.5	Dual	lbs.	2720	2860	3000(E) 119	3115	3245	3415(F) 123	3490	3615	3750(G) 126					
	Single		2895	3040	3195(E) 121	3315	3450	3640(F) 125	3715	3845	3970(G) 128					
245/70R19.5	Dual	lbs.			3415	3515	3655	3860(F) 127	3940	4075	4300(G) 131	4345	4540(H) 133			
	Single				3640	3740	3890	4080(F) 129	4190	4335	4540(G) 133	4620	4805(H) 135			
265/70R19.5	Dual	lbs.			3750	3930	4095	4300	4405	4415	4675(G) 134					
	Single				3970	4180	4355	4540	4685	4850	5070(G) 137					
285/70R19.5	Dual	lbs.			4200	4410	4615	4820	5020	5220	5420	5615	5810	6005(H) 143		
	Single				4470	4695	4915	5130	5345	5560	5770	5980	6185	6395(H) 145		
8R19.5	Dual	lbs.	2460	2570	2680(D) 115	2785	2890	3000(E) 119	3100	3200	3305(F) 122					
	Single		2540	2680	2835(D) 117	2955	3075	3195(E) 121	3305	3415	3525(F) 124					
8.25R20	Dual	lbs.	3270	3410	3550	3690	3860(E) 127	4005	4150	4300(F) 131	4425	4550	4675(G) 134			
	Single		3370	3560	3730	3890	4080(E) 129	4235	4390	4540(F) 133	4675	4810	4940(G) 136			
9.00R20	Dual	lbs.	3860(D) 127	4045	4230	4410(E) 132	4585	4760	4940(F) 136	5080	5220	5355(G) 139				
	Single		4080(D) 129	4280	4480	4675(E) 134	4850	5025	5205(F) 138	5360	5515	5675(G) 141				
10.00R20	Dual	lbs.	4380	4580	4760	4950	5205(F) 138	5415	5625	5840(G) 142	5895	5950	6005(H) 143			
	Single		4530	4770	4990	5220	5510(F) 140	5730	5950	6175(G) 144	6320	6465	6610(H) 146			
11.00R20	Dual	lbs.	4780	4990	5190	5390	5675(F) 141	5785	5895	6005(G) 143	6265	6525	6780(H) 147			
	Single		4940	5200	5450	5690	6005(F) 143	6205	6405	6610(G) 146	6870	7130	7390(H) 150			
12.00R20	Dual	lbs.	5440	5680	5910	6140	6360	6610(G) 146	6790	6970	7160(H) 149	7390	7610(J) 151			
	Single		5620	5920	6200	6480	6740	7160(G) 149	7380	7600	7830(H) 152	8050	8270(J) 154			
11.00R22	Dual	lbs.	5080	5300	5520	5730	5840(F) 142	6095	6350	6610(G) 146	6790	6970	7160(H) 149			
	Single		5240	5520	5790	6040	6395(F) 145	6650	6910	7160(G) 149	7380	7600	7830(H) 152			
255/70R22.5	Dual	lbs.			3970	4110	4275	4410	4455	4610	4675(G) 134	4915	5070(H) 137			
	Single				4190	4370	4550	4675	4895	5065	5205(G) 138	5400	5510(H) 140			
275/70R22.5	Dual	lbs.	3895	4115	4335	4550	4765	4975	5180	5390	5590	5795	5995	6195	6395(H) 145	
	Single		4230	4470	4705	4940	5175	5400	5630	5850	6075	6295	6510	6730	6945(H) 148	
245/75R22.5*	Dual	lbs.	3160	3315	3525	3615	3765	3970	4055	4195	4300(G) 131					
	Single		3470	3645	3860	3975	4140	4300	4455	4610	4675(G) 134					
265/75R22.5**	Dual	lbs.	3525	3705	3860	4040	4205	4410	4525	4685	4805(G) 135					
	Single		3875	4070	4300	4440	4620	4805	4975	5150	5205(G) 138					
295/75R22.5***	Dual	lbs.	4095	4300	4540	4690	4885	5070(F) 137	5260	5440	5675(G) 141					
	Single		4500	4725	4940	5155	5370	5510(F) 140	5780	5980	6175(G) 144					
295/80R22.5	Dual	lbs.	4360	4610	4855	5095	5335	5570	5805	6035	6265	6490	6715	6940(H) 148		
	Single		4920	5200	5475	5750	6020	6285	6545	6810	7065	7320	7575	7830(H) 152		
315/80R22.5	Dual	lbs.			5675	5840	6070	6395	6545	6770	6940	7210	7610	8010	8270(L) 150	
	Single				6175	6415	6670	6940	7190	7440	7610	7920	8270	8810	9090(L) 154	
315/80R22.5'	Dual	lbs.	5030	5315	5595	5875	6150	6420	6690	6955	7220	7480	7740	8000	8255(L) 150	
	Single		6090	6440	6780	7115	7450	7780	8105	8425	8745	9065	9375	9690	10000(L) 154	
9R22.5	Dual	lbs.	3270	3410	3550	3690	3860(E) 127	4005	4150	4300(F) 131	4425	4550	4675(G) 134			
	Single		3370	3560	3730	3890	4080(E) 129	4235	4390	4540(F) 133	4675	4810	4940(G) 136			

¹ For M320Z only. Maximum speed = 55 mph

*Equivalent to Michelin 235/80R22.5

**Equivalent to Michelin 255/80R22.5

***Equivalent to Michelin 275/80R22.5

NOTE: All data shown here is approximately what you would find under normal conditions and is subject to change without notice.

Though every effort has been taken to ensure the accuracy of this data shown here, legal responsibility cannot be accepted by Toyo Tire U.S.A. Corp. or Toyo Tire & Rubber Co., Ltd., for any damage or loss coming from any undetected errors or any misprint.

LOAD AND INFLATION TABLES

TBR Load Inflation Tables

TIRE LOAD LIMITS (LBS.) AT VARIOUS COLD INFLATION PRESSURES

- NEVER exceed the sidewall markings for the maximum loads and inflation pressures

Note: Letters in parentheses denote Load Range for which Bold Face loads are maximum. International Load Index numbers are shown after the Load Range.

Tire Size	PSI		70	75	80	85	90	95	100	105	110	115	120	125	130
10R22.5	Dual	lbs.	3860	4045	4230	4410(E) 132	4585	4760	4940(F) 136	5075	5210	5355(G) 139			
	Single		4080	4280	4480	4675(E) 134	4850	5025	5205(F) 138	5360	5515	5675(G) 141			
11R22.5	Dual	lbs.	4380	4580	4760	4950	5205(F) 138	5415	5625	5840(G) 142	5895	5950	6005(H) 143		
	Single		4530	4770	4990	5220	5510(F) 140	5730	5950	6175(G) 144	6320	6465	6610(H) 146		
12R22.5****	Dual	lbs.	4780	4990	5190	5390	5675(F) 141	5785	5895	6005(G) 143	6265	6525	6780(H) 147		
	Single		4940	5200	5450	5690	6005(F) 143	6205	6405	6610(G) 146	6870	7130	7390(H) 150		
285/75R24.5	Dual	lbs.	4135	4340	4540	4740	4930	5205(F) 138	5310	5495	5675(G) 141				
	Single		4545	4770	4940	5210	5420	5675(F) 141	5835	6040	6175(G) 144				
11R24.5	Dual	lbs.	4660	4870	5070	5260	5510(F) 140	5675	5840	6005(G) 143	6205	6405	6610(H) 146		
	Single		4820	5070	5310	5550	5840(F) 142	6095	6350	6610(G) 146	6790	6970	7160(H) 149		

1 For M320Z only. Maximum speed = 55 mph

*Equivalent to Michelin 235/80R22.5

**Equivalent to Michelin 255/80R22.5

***Equivalent to Michelin 275/80R22.5

****Equivalent to Michelin 295/80R22.5

Tire Size	PSI		70	75	80	85	90	95	100	105	110	115	120	125	130
14/80R20	Single	lbs.	5870	6205	6535	6860	7180	7495	7810	8120	8430	8735	9040(J)		
385/65R22.5	Single	lbs.	6380	6720	6940	7350	7650	8050	8230	8510	8820	9050	9370(J) 158		
385/65R22.5	Single	lbs.	6380	6720	6940	7350	7650	8050	8230	8510	8820	9050	9370(J) 160		
425/65R22.5	Single	lbs.	7590	7990	8270	8740	100	9370	9790	10100	10500	10700	11400(L) 165		

Low Platform Trailer

Tire Size	PSI		70	75	80	85	90	95	100	105	110	115	120	125	130
8.25R15TR	Dual	lbs.	2700	2810	2930	3040	3150	3260	3360	3525(F) 124	3635	3745	3860(G) 127		
	Single		2780	2930	3080	3200	3340	3470	3590	3750(F) 126	3860	3970	4080(G) 129		
8.25R15TR	Dual	lbs.	3565	3770	3970	4165	4360	4555	4745	4935	5120	5305	5490	5675(J) 141	
	Single		3775	3990	4205	4410	4620	4825	5025	5225	5425	5620	5815	6010(J) 143	
10.00R15TR	Dual	lbs.	3660	3830	3980	4130	4300(F) 131	4470	4640	4805(G) 135					
	Single		3780	3980	4170	4370	4540(F) 133	4715	4890	5070(G) 137					
10.00R15TR	Dual	lbs.	4020	4245	4470	4695	4915	5130	5345	5560	5770	5980	6185	6395(J) 145	
	Single		4365	4615	4855	5100	5335	5575	5805	6040	6265	6495	6720	6945(J) 148	
215/75R17.5	Dual	lbs.	2855	3015	3175	3330	3490	3645	3795	3945	4095	4245	4390	4540(H) 133	
	Single		3020	3190	3360	3525	3690	3855	4015	4175	4335	4490	4650	4805(H) 135	
235/75R17.5	Dual	lbs.	3570	3770	3970	4170	4365	4560	4750	4940	5125	5310	5495	5680(H) 141	
	Single		3770	3985	4195	4405	4610	4815	5015	5215	5415	5610	5805	6000(H) 143	

NOTE: All data shown here is approximately what you would find under normal conditions and is subject to change without notice.

Though every effort has been taken to ensure the accuracy of this data shown here, legal responsibility cannot be accepted by Toyo Tire U.S.A. Corp. or Toyo Tire & Rubber Co., Ltd., for any damage or loss coming from any undetected errors or any misprint.